

BU/2 EM 8-00+03 S0 AS SB 1.5mm FG

Product information

Article number	01090062
Standard width	3000 mm
Maximum width	

Construction

Top face material	PU
Surface structure	Matt finish
Coating thickness	0.3 mm
Colour	s. blue
Bottom cover face	
Surface structure	Impregnated fabric
Colour	white
Tension member material	Polycester fabric
Number of fabric plies	2

Technical data

Total thickness	1.50 mm
Weight	1.6 kg/m ²
Force elongation at 1%	8 N/mm
Min. Pulley Ø	15 mm
Friction coefficient of bottom face	0.25
Permissible temperature	-20° C/+90° C
Top face Hardness	92 ShA
Antistatic	✓

Technical data

Lateral stiffness	✓
Troughable	
Suitable for curves	
Food grade (FG)	✓
Anti-microbial (AM)	
Heat resistant (HR)	
Fray-less (FL)	
Flame-retardant (FR)	
Energy saving (ES)	
Noise development	Regular
Belt support	Support slider bed

Joining Technical Info

Joint type	Finger Joint
Upper platen Temp.	162 ° C
Lower platen Temp.	158 ° C
Curing time	4 min
Pressure	2 Bar

The physical data in this data sheet is approximate, can alter depending on production environments and is established at approx. 20 °C (68 °F). Fluctuations in climate can cause variations. Ino Belt excludes any liability for the incorrect use of the above stated information.