

Product Data Sheet

Specification : TAN EP135 1200W×3P×RT×BARE 100M

Item		Unit	Standard		Structure
Dimensions	Width	mm	1200	±1%	
	Length	M	100	+free -0	
	Top Cover (a)	mm	3.2	+free -0.3	
	Bottom Cover (b)	mm	0	+free -0.3	
	Carcass (c)	mm	3.1	±0.3	
	Total Thickness (T)	mm	7.1	±1	
Belt	Carcass Type	-	EP		
	Number of Ply	-	3		
	Breaking Strength	kgf/cm	400	min	
	Breaking Elongation	%	4	min	
	Elongation at 10% Load	%	3	max	
	Temperature Range	°C	-20~60		
	Edge	-	Cut Edge		
Adhesion	Top / Fabric	kgf/inch	12.0	min	
	Fabric / Fabric	kgf/inch	12.0	min	
	Bottom / Fabric	kgf/inch	11.0	min	
Rubber	Tensile Strength	kgf/cm ²	90	min	
	Elongation	%	500	Min	
	Abrasion	mm ³	350	max	
	Hardness	A shore	52	±3	
	Ozone (50pphm×40°C×20%×96hr)		No Crack		
Remark	*Tan Rough Top *Min. Pulley Diameter: Ø 250 mm				



HSIN YUNG CHIEN CO., LTD.

No.294 Nan-Kung 3 Rd., Nan Kung Industrial Zone Nantou 540, Taiwan
Web site : www.hyc-king.com

ISO 9001
ISO 14001
OHSAS 18001

Product Data Sheet