

REOClean F30 DB

Product Datasheet

Product information

Article number	04061004
Standard width	1420 mm
Maximum width	

Construction

Top face material	PU
Surface structure	Glossy
Coating thickness	
Colour	d. blue
Bottom cover face	
Surface structure	PU
Colour	d. blue
Tension member material	Aramid cords
Number of fabric plies	N/A

Technical data

Total thickness	3.0 mm
Weight	3.7 kg/m ²
Force elongation at 1%	20 N/mm
Min. Pulley Ø	90 mm
Friction coefficient of bottom face against steel panel according ISO21182	0.60
Permissible operating temperature	-30°C/+100°C
Hardness of top face coating as per DIN 53505 (Shore A)	95 ShA
Antistatic	

Properties

Lateral stiffness	√
Troughable	
Suitable for curves	
Food grade (FG) :FDA	√
Anti-microbial (AM)	√
Heat resistant (HR)	
Fray-less (FL)	√
Flame-retardant (FR) ISO340	
Energy saving (ES)	
Suitable for knife edges	
Noise development	Regular
Belt support	Support slider bed

Jointing Technical Info

Joint type	Butt Joint
Upper platen Temp.	N/A
Lower platen Temp.	N/A
Curing time	N/A
Pressure	N/A

The physical data in this data sheet is approximate, can alter depending on production environments and is established at approx. 20 °C (68 °F). Fluctuations in climate can cause variations. Ino Belt excludes any liability for the incorrect use of the above stated information.

no Belt - total belting solution

Last edit date: 2018.12.25