


Products datasheet



UPRO 2/15B-M

Schematic structure



6D:392287

Belt Applications

General conveying belt, Food industry

Fabric information

Number of plies	2
Top fabric	Polyester monofilament, with lateral stability
Bottom fabric	Polyester monofilament, with lateral stability, antistatic

Basic technical data

Total thickness	1.5 mm	<i>0.059 in.</i>
Weight	1.7 kg/M²	<i>0.35 lbs./sq.ft.</i>
Standard width	3200 mm	<i>126 in.</i>
Tension for		
1% elongation	8 N/mm	<i>46 lbs./ in.</i>

Belt support

Roller	Yes
Silder bed	Yes
Troughed	No

Minimum pulley diameter

Normal flection	20 mm	<i>0.79 in.</i>
Counter flection	30 mm	<i>1.18 in.</i>

Suggested joint methods

One ply finger

Detailed technical data

Top cover	
-Thickness	0.4 mm <i>0.016 in.</i>
-Material	Polyurethane
-Hardness	Shore A86
-Color	Blue
-Surface	Matt finish
Middle cover	
-Thickness	0.2 mm <i>0.008 in.</i>
-Material	Polyurethane
-Hardness	Shore A86
-Color	Blue
Bottom cover	
-Material	Fabric impregnation PU
-Color	Transparent

Chemical resistant and other characteristics

* Top cover permitted according to the FDA-prescriptions to paragraph 177.2600 for transport of all unpackaged foodstuffs

* Good resistance to animal, mineral and vegetable oil and fat

* Temperature range of -20°C to +80°C *-4°F to 176°F*